



HiMax™ FAHM116

[AHM, 450, -45/+45]



Product Data Sheet

Fabric Construction

Fibre Type: Aramid
Construction: -45/+45
Fabric Weight: 463 gsm +/- 5%

Stitching Fibre

Stitching Thread: Texturised Polyester
Stitch DTex: 78
Stitch Gauge: 6.0 gg
Stitch Length: 2 mm
Stitch Type: Pillar
Stitch Weight: 9 gsm


Ply Construction

-45 Ply

Fibre Specification: Aramid
Fibre Tex: 340 tex
Gauge: 12 gg
Ply Weight: 227 gsm

+45 Ply

Fibre Specification: Aramid
Fibre Tex: 340 tex
Gauge: 12 gg
Ply Weight: 227 gsm



Customisation

Customer Code and Description:	Customer Specified
Fabric Width:	1270mm (+/- 5mm) - or tapes on application
Tracer Threads / Tapered Edges:	Customer Specified
Approved Fibres:	On Application
Roll Weight / Length:	Customer Specified
Cardboard Core:	Customer Specified
Packaging:	Customer Specified



HiMax™ FAHM116

[AHM, 450, -45/+45]



Product Data Sheet

For more information

Hexcel is a worldwide supplier of composite materials to aerospace and industrial markets.

Our comprehensive range includes:

- HexTow® carbon fibres
- HexFlow® RTM resins
- Acousti-Cap® sound attenuating honeycomb
- HexForce® reinforcements
- Redux® adhesives
- Engineered core
- HiMax™ non-crimp fabrics
- HexTool® tooling materials
- Engineered products
- HexPly® prepregs
- HexWeb® honeycombs
- HexMC® moulding compounds

For quotes, orders and product information call +44 116 275 2200. For other worldwide sales office telephone numbers and a full address list, please go to:

<http://www.hexcel.com/contact/salesoffice>